

**31HP + 400+CFM + 1200PSI + 245°F + 2 Wands =
The numbers add up to your next truckmount!**

BOXXER XL

Key Features

Perfectly Powered

31 HP Air Cooled Engine - Industrial engine delivers maximum power in an incredibly fuel efficient fashion.

Quietest in its Class

Innovative Air Flow - Routing and controlling concepts make it 20% quieter than a comparable truckmount.

Extreme

Vacuum and Water Extraction Recovery - 400+ CFM for faster drying, faster extraction! Direct coupler driven for maximum power transfer.

Uncompromising

Cleaning Solution Temperature - 245° F Temperature rating with 185° F at 1.25 GMP continuous flow.

Completely

Dual Wand Capable - plumbed and prepared for you to double your productivity when you need to!

Patented

Heat Control System, ADC Control Diverter Manages heat for more consistent temperature delivery, virtually eliminates dumping trash water during cleaning delays and water extraction.

Simpler

Maintenance - "Arms Length" design and removable magnetic panels allow for easy access to crucial components and serviceable parts.



We've Got Your Back!



HydraMaster warranty service is rated #1 by distributor mechanics!

Applications:

- Dual Wand Cleaning
- Residential, Large Commercial Carpet Cleaning
- Pressure Washing with full waste recovery capabilities
- Upholstery Cleaning
- Concrete, Stone, Tile and Grout Cleaning
- Hard Surface high pressure cleaning

Made in the USA

HydraMaster
We've Got Your Back

www.hydramaster.com | 800.426.1301 | 425.775.7272



**31HP + 400⁺ CFM + 1200PSI +
245°F + 2 Wands =**
The numbers add up to your next truckmount!



Standard Equipment

- Runtime hour meter
- Chemical flow meter (0-10 GPH)
- Chemical flow control valve
- 5 gallon chemical jug
- Vacuum gauge (0-30" Hg)
- Solution pressure gauge (0-1,500 PSI)
- Solution pressure adjustment
- Pre-wired pump-in switch
- Pre-wired APO Switch
- Fresh water inlet
- Water system drain valve
- Stainless steel carpet cleaning wand
- Diverter valve (with ADC heat control)
- Diverter/clutch package for flood work
- Electrical circuit protection
- Pump clutch switch
- Solution temperature control selector
- Two solution outlets
- Solution Hose Length: 100 ft x 1/4"
- Vacuum Hose Length: 100 ft x 2"
- Wand Whip Line: 10 ft x 1-1/2"
- 50 ft water supply line
- Recovery Tank: 70 gallon MaxxAir™
- Battery box
- Van installation kit
- Operation & maintenance manual
- Embroidered HydraMaster jacket

Optional Accessories

- Dura-Flow™ APO (auto pump-out)
- RX-20 rotary carpet extractor
- RX-15H rotary hard surface wand
- DriMaster 3 upholstery tool
- HydraCradle reel/tank combo
- 100 gallon MaxxAir™ recovery tank, aluminum powder coated
- Thru-floor exhaust kit
- Evolution Truckmount Wand



100 Gallon MaxxAir™ Waste Tank Option Includes a FREE 1 1/2" Evolution Wand Upgrade.

Scan for more information.



Engine: 31HP Briggs & Stratton® Vanguard™ Air Cooled Engine

- Fuel-efficient — 1.6 GPH at recommended 3000 RPM
- Keyed ignition
- Nationwide Serviceability
- Operating at 3000 RPM

Vacuum: 4007 Dominator™ Tri-Lobe Blower, 400+ CFM

- Direct Coupler Driven
- HydraMaster exclusive design
- Dual oil bath design with sight level windows
- Durable helical gear drive



Solution Pump: Plunger pump with 1200 operating PSI

- General HTX-1813 4.0 GPM solution pump
- Electric clutch-control

Heating System: Thermal Capture and Heat Exchange System

- Full Divert Tube and Finned Tube Heat Exchanger
- Automatic Diverter Control (ADC) Temperature Control
- Attains 245°F Temperature (185°F continuous flow at 1.25 GPM)
- Patented design and function: US Patent No. 8,032,976
- Easy to access and remove core for easy cleaning and maintenance



Machine Specifications

- Dimensions: 24"W x 39"H x 41"D
- Weight: 800 lbs
- Chemical System: last-step chemical injection, meter controlled
- Wand Capacity: Dual



Made in the USA

HydraMaster
We've Got Your Back

