Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/28/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Trade name O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.

Product code ORC72414

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Cleaner

Details of the supplier of the safety data sheet

O'Reilly Auto Parts 233 South Patterson Springfield, Missouri 65802 T 417-862-2674

Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 2

Gases under pressure Compressed gas

Acute toxicity (oral) Category 3 Acute toxicity (dermal) Category 3

Serious eye damage/eye irritation Category 2A

Full text of H- and EUH-statements: see section 16

Specific target organ toxicity (single exposure) Category 1

Specific target organ toxicity — Single exposure, Category 3, Narcosis

H223 Flammable aerosol

H280 Contains gas under pressure; may explode if heated

H301 Toxic if swallowed

H311 Toxic in contact with skin

H319 Causes serious eye irritation

H370 Causes damage to organs

H336 May cause drowsiness or dizziness

Label elements

GHS US labeling Hazard pictograms (GHS US)

Precautionary statements (GHS US)











Signal word (GHS US) : Danger

Hazard statements (GHS US) : H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H370 - Causes damage to organs

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray

P264 - Wash affected areas thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor,physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor.

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

28/10/2022 EN (English US) 1/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	85 – 95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methanol	(CAS-No.) 67-56-1	10 – 30	Flam. Liq. 2, H225 STOT SE 1, H370
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 – 10	Press. Gas (Comp.), H280

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation

: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact

Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: Causes damage to organs.

Symptoms/effects after inhalation

: Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/effects after eye contact

: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

T : '/ "

Symptoms/effects after ingestion

 Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

28/10/2022 EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug

the leak, cut off the supply.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not spray on an open flame or other ignition source. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe

dust,fumes,gas,mist,vapor spray.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder

separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact. Observe very strict hygiene - avoid contact. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity

should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.		
No additional information available		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	9000 mg/m ³	
ACGIH OEL TWA [ppm]	5000 ppm	

28/10/2022 EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACGIH OEL STEL	54000
ACGIH OEL STEL [ppm]	30000 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	9000 mg/m³
OSHA PEL (TWA) [2]	5000 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	9000 mg/m³
NIOSH REL TWA [ppm]	5000 ppm
NIOSH REL (Ceiling)	54000 mg/m³
NIOSH REL C [ppm]	30000 ppm
Methanol (67-56-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	262 mg/m³
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL	328 mg/m³
ACGIH OEL STEL [ppm]	250 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	260 mg/m³
OSHA PEL (TWA) [2]	200 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	260 mg/m³
NIOSH REL TWA [ppm]	200 ppm
NIOSH REL (Ceiling)	325 mg/m³
NIOSH REL C [ppm]	250 ppm
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1188 mg/m³
ACGIH OEL TWA [ppm]	500 ppm
ACGIH OEL STEL	1782 mg/m³
ACGIH OEL STEL [ppm]	750 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	2400 mg/m³
OSHA PEL (TWA) [2]	1000 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	590 mg/m³
NIOSH REL TWA [ppm]	250 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

Excellent resistance:

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):

28/10/2022 EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas Appearance : Liquid.

Color

Freezing point : -78 °C (Lowest Component-Acetone)

Boiling point : 56.11 °C (Lowest Component-Acetone)

Flash point : -18 °C (Lowest Component-Acetone)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.82
Density : 0.82 g/cm³

Solubility : Poorly soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Partition coefficient n-octanol/water (Log Kow) : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Heating may cause a fire. Heating may cause an explosion.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 45 %

Gas group : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

28/10/2022 EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION	11: Toxico	logical in	formation
OE O I I O I I	I I I I OAIOO	logioai iii	- Cilliani

11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed. Acute toxicity (dermal) : Toxic in contact with skin.

Acute toxicity (inhalation) : Not classified

ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight

ATE 00 (actitial)	300 mg/kg body weight	
Methanol (67-56-1)		
LD50 oral rat	≥ 2528 mg/kg body weight application as 50% aqueous solution	
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors	
LC50 Inhalation - Rat	128.2 mg/l/4h Air	
ATE US (dermal)	17100 mg/kg body weight	
ATE US (vapors)	128.2 mg/l/4h	
ATF US (dust, mist)	128.2 mg/l/4h	

. = 0.1		
Acetone (67-64-1)		
5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)		
20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)		
71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)		
30000 ppm/4h (Rat; Experimental value)		
5800 mg/kg body weight		
20000 mg/kg body weight		
30000 ppmV/4h		
71 mg/l/4h		
71 mg/l/4h		

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity Not classified

STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.

Methanol (67-56-1)		
STOT-single exposure	Causes damage to organs.	
Acetone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified	

Aspiration hazard : Not classified Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.

Symptoms/effects : Causes damage to organs.

Symptoms/effects after inhalation Shortness of breath. May cause drowsiness or dizziness.

Repeated exposure to this material can result in absorption through skin causing significant Symptoms/effects after skin contact

health hazard. Toxic in contact with skin.

: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Symptoms/effects after eye contact

Causes serious eye irritation.

Symptoms/effects after ingestion Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

SECTION 12: Ecological information

12.1. Toxicity

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)	

28/10/2022 EN (English US) 6/11

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semistatic system, Fresh water, Experimental value, Locomotor effect)	
Acetone (67-64-1)		
LC50 - Fish [1]	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)	
EC50 - Crustacea [1]	8800 mg/l (48 h; Daphnia pulex)	
LC50 - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
TLM - Fish [1]	13000 ppm (96 h; Gambusia affinis; Turbulent water)	
TLM - Fish [2]	> 1000 ppm (96 h; Pisces)	
Threshold limit - Other aquatic organisms [1]	3000 mg/l (Plankton)	
Threshold limit - Other aquatic organisms [2]	28 mg/l (Protozoa)	
Threshold limit - Algae [1]	7500 mg/l (Scenedesmus quadricauda; pH = 7)	
Threshold limit - Algae [2]	3400 mg/l (48 h; Chlorella sp.)	
12.2. Persistence and degradability		

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.			
Persistence and degradability	Not established.		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
Persistence and degradability	Biodegradability: not applicable. Not established.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
Methanol (67-56-1)			
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water. Not established.		
Biochemical oxygen demand (BOD)	0.6 − 1.12 g O₂/g substance		
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance		
ThOD	1.5 g O ₂ /g substance		
Acetone (67-64-1)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance		
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance		
ThOD	2.2 g O ₂ /g substance		
BOD (% of ThOD)	(20 day(s)) 0.872		

12.3. Bioaccumulative potential

2.3. Bioaccumulative potential			
O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.			
Bioaccumulative potential	Not established.		
Carbon Dioxide, Liquefied, Under Pressure (1	Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
Partition coefficient n-octanol/water (Log Pow)	0.83 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.		
Methanol (67-56-1)			
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)		
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.		
Acetone (67-64-1)			
BCF - Fish [1]	0.69 (Pisces)		
BCF - Other aquatic organisms [1]	3		
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)		
Bioaccumulative potential	Not bioaccumulative. Not established.		

12.4. **Mobility in soil**

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Ecology - soil	Not applicable (gas).
Methanol (67-56-1)	
Surface tension	No data available in the literature
organic Carbon Normalized Adsorption -0.890.21 (log Koc, Calculated value)	
Ecology - soil	Highly mobile in soil.

28/10/2022 EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
Surface tension	0.0237 N/m (20 °C)

12.5. Other adverse effects

Effect on global warming : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

US DOT (ground) (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

Flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

Class (DOT)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 24-HOUR EMERGENCY INFORMATION: CHEMTREC (800) 424-9300

Other information : No supplementary information available.

Transport by sea

UN-No. (IMDG) : 1950

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : 1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

15.1. US Federal regulations

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
	Fire hazard
	Immediate (acute) health hazard
	Sudden release of pressure hazard

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

28/10/2022 EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard	
Methanol (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	5000 lb	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard	
SARA Section 313 - Emission Reporting	1 %	
Acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard	

15.2. International regulations

CANADA

ANAMA				
O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.				
WHMIS Classification	Class B Division 5 - Flammable Aerosol			
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)				
Listed on the Canadian DSL (Domestic Substances List)				
Methanol (67-56-1)				
Listed on the Canadian DSL (Domestic Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Acetone (67-64-1)				
Listed on the Canadian DSL (Domestic Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

EU-Regulations

Methanol (67-56-1)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. **National regulations**

Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.()	
U.S California - Proposition 65 - Carcinogens List	Yes
U.S California - Proposition 65 - Developmental Toxicity	Yes

28/10/2022 EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OIDEILL VIC CARR & CHOKE CLEANER 43 F O7 ()

No	No	No	No	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)				
State or local regulations U.S California - Proposition 65				
U.S California - Proposition 65 - Reproductive Toxicity - Male		Yes		
U.S California - Proposition 65 - Reproductive Toxicity - Female		No		

Wethanor	(07-30-1)
ILS - Calif	ornia -

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Acetone (67-64-1)

710010110 (07 01 1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	
Yes	Yes	No	Yes	

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

State or local regulations

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List U.S. Pennsylvania RTK (Right to Know) List

Methanol (67-56-1)

State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65

Benzene 71-43-2

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information : None

Full text of H-phrases:

٠,,	tt of 11 philaded.			
	H223	Flammable aerosol		
	H225	Highly flammable liquid and vapor		
	H280	Contains gas under pressure; may explode if heated		
	H301	Toxic if swallowed		
	H311	Toxic in contact with skin		
	H319	Causes serious eye irritation		
	H336	May cause drowsiness or dizziness		
	H370	Causes damage to organs		

NFPA health hazard

28/10/2022 EN (English US) 10/11

^{: 2 -} Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

28/10/2022 EN (English US) 11/11